

# SAN-6700 CMOS

## 700TVL Bullet IR Camera



### Key features

- 1/3" CMOS
- 700TVL high resolution
- 3.6mm Lens
- Up to 15m/30m IR range
- IP66 weatherproof

SAN-6700 CMOS	
Camera	
Image Sensor	1 / 3" CMOS
Signal System	PAL / NTSC
Effective Pixels	PAL: 976 (H) x 584 (V), NTSC: 976 (H) x 496 (V)
Min. Illumination	0.01 Lux(0.0Lux IR ON)
Shutter speed	1 / 50(1 / 30) s to 1 / 100,000 s, NTSC: 1 / 60 s to 1/100,000 s
Lens	3.6mm (4mm, 6mm, 8mm, 16mm optional)
	Angle of View: 76.88°(3.6mm), 50.1°(6mm), 36.8°(8mm), 24.33°(12mm), 18.4°(16mm)
Lens Mount	M12
Day & Night	ICR
Synchronization	Internal synchronization
Video Frame Rate	25 fps (PAL) / 30 fps (NTSC)
IR Distance	45 Ft
S / N Ratio	More than 52dB
General	
Working Temperature / Humidity	-10 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12 VDC±10%
Power Consumption	Max. 4.5W
Weather Proof Ratings	IP66
IR Range	Up to 15/20m
Weight	800 g (1.76 lb)
IR Distance	45 ft.